



909 B DOSIMETER CHARGER

With Two AA 1.5V Batteries

Easier charging, viewing, dosimeter protection and improved accuracy... these are the biggest reasons that the 909 B Dosimeter Charger is the best value on the market today!



Product Description

The 909 B Charger reading light reduces re-zeroing time and effort by eliminating the need to remove the dosimeter from the charger for reading. Simply view the scale while the dosimeter is resting lightly on the charger contact after re-zeroing. Reading in the same orientation as charging also minimizes the

effect that gravitational induced fiber movement has on dosimeter accuracy and precision. The 909 B Charger charging contact has a positive mechanical stop. This design feature makes it virtually impossible to damage dosimeters through excessive charging force.

Feature List

- 01 UNIVERSAL COMPATIBILITY**
Charges any Direct-Reading Dosimeter
- 02 STANDARDS COMPLIANCE**
Meets ANSI N42.6 requirements
- 03 BATTERY-POWERED**
Operates on two AA 1.5 V batteries
- 04 RESIDUAL CHARGE REMOVAL**
Effectively removes residual charge to prevent spurious upscale fiber movement
- 05 EASY VIEWING**
Includes a reading light for convenient charging and viewing
- 06 ENHANCED ACCURACY**
Removes residual static charge for improved accuracy

Specs

CONTROLS	WEIGHT
One Turn Potentiometer	10.6 Oz (302gm)
POWER	WIDTH
(2) AA 1.5v Batteries	4" (10.2cm)
CHARGING VOLTAGE	LENGTH
40 V To 220 V	4" (10.2cm)
READING	HEIGHT
Spring Loaded Push Rod	3.5" (8.9cm)
OPERATING TEMPERATURE	CASE
0 — 120 F (-18 — 49 C) Lamp: LED Ultra Bright P/N: 87-90007	ABS Plastic